

# EPP DOMES






## Sun Fighter

Handles Glare & Reflections  
from Water, Concrete & Surfaces

Vandalproof - Weatherproof - Waterproof



<b>Model</b>	BPSF
Image Device	Sony Vertical double-density 1/3" CCD
Total Pixels	NTSC / 811(H) x 508(V), PAL / 795(H) x 596(V)
Effective Pixels	NTSC / 768(H) x 494(V), PAL / 752(H) x 582(V)
Electronic Shutter	NTSC / 1/60 ~ 1/100,000sec Auto, PAL / 1/50 ~ 1/100,000sec Auto
Scanning System	2:1 Interlace
Horizontal Resolution	480TV lines
Low Lux Sensitivity	0.5Lux
S/N Ratio	More than 45dB(AGC off)
AGC	MIN / AWT / MAX
Sensitivity	Color 0.004Lux, B/W 0.001Lux AGC Max, DSS Maz
WDR	OFF/ON (Dynamic range x 64)
Image Effect	B/W, Nega/Posi, H/V Mirror, Sharpness, Freeze
Privacy Zone	8 Points
White Balance	ATW / Push / User
Gamma Correction	y=0.45
Digital Slow Shutter	OFF/ON (2x, 4x, 8x, 10x, 20x, 40x, 80x, 160x)
Weatherproof	IP66
Operating Temperature	-10°C ~ +45°C
Mount	Ceiling Mount Kit Included
Power Supply	Dual Power ( DC 12V / AC 24V)
Lens Options	Varifocal Lens 2.8~11mm, (fixed lens option)
Other Functions	Bright control, Color adjustment, IR remove, BLC, DSS 160x / Day & Night (Adjustable at 10,5, 3Lux)



201 North Elm Street  
Kemp, Texas 75143  
Toll Free: 1-866-301-CCTV  
Phone: 903-498-3240  
Fax: 903-498-8989  
Website: [www.rugged-cctv.com](http://www.rugged-cctv.com)  
E-mail: [techsupport@rugged-cctv.com](mailto:techsupport@rugged-cctv.com)