

Speakers

RCS8 Ceiling Speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 8" paper speaker cone, 3 Watts RMS max.
- Built in RLT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.



RCS4 Ceiling / Flush Mount Speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 4" mylar speaker cone, 3 Watts RMS max.
- Built in RLT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.

RWS4 Wall / Surface Mount Speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 4" mylar speaker cone, 3 Watts RMS max.
- Built in RLT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.



RHS5 Horn Speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 5" horn speaker, 3 Watts RMS max.
- Built in RLT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.
- Not recommended for outdoor use.

ROS6 Outdoor Speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 6" diagonal horn speaker, 3 Watts RMS max.
- Tough, cast aluminum housing.
- Built in tamper switch.
- Built in RLT870 70v line transformer.
- Easy cable termination.



**Directly Mounts to
Double Gang Box**

RTW1 Two Way Microphone / Speaker Omni-directional pre-amplified microphone and speaker for use in two way surveillance systems.

- Stainless Steel cover. Fits double gang boxes.
- Low noise MOSFET pre-amplifier.
- Line level unbalanced output. Adjustable gain.
- Limiter and treble boost circuits selectable on/off.
- Built in 2.25" speaker 0.5W and RLT870 70v line transformer.
- Power: 12V DC @ 10mA. On board voltage regulator.