

DVR / PTZ Controller

3-Axis System Controller




FEATURES

- Control up to 255 Cameras & 255 DVRs
- Multiple protocol supported in each channel
- RS-485 / RS-422 communication (Tx : 3 port, Trx :1 port)
- Programmable user preferences (Preset, Tour, Pattern, etc.)
- Easy upload programmed data via serial communication
- Built-in 2 lines character LCD
- User password support
- Programmable transmission speed for each ID (2.4-57.6kbps)
- Operate with 9V battery

SPECIFICATIONS

Model	iC-1000
Keyboard Communication	Interface : RS-485 (Tx 3 port, Trx 1 port)
	Pan/Tilt operating distance : 4700 ft (1029m) No 24 AWG wire
	Multiple Protocol Support (Baud rate selectable)
	Terminal Block (8p connector)
Keyboard Keypad	Rubber button
	Numeric keypad and camera function key
Joystick	Proportional 3-Axis, variable speed with zoom
Input Voltage	12VDC or 9V battery (battery mode)
Power Consumption	Max.140mA
LCD Display	2 lines character LCD
Operating Temperature	0° to 45°C
Humidity	10%-70% RH
Certification	CE, FCC, RoHS



RS-485 / RS-422 communications
- Built-in 3ports of Tx/Rx, 1port of Trx



9V Battery

- Operate with a 9V battery or power adapter

DIMENSIONS

