

Long Range High Bandwidth Wireless

900' - 9800' range

## **Features**

- 900' 9800' Wireless transmission range with line of sight
- Completely Plug-N-Play connection. Simply aim them at each other and they will connect automatically.
- POE power injector included with each panel
- Qualcomm Atheros AR9344 600Mhz Chipsets, and have 64Mb of DDR2 Memory, as well as 8Mb of Flash Memory for saving settings.
- Encrypted using WEP 64/128 bits, WPA, WPA2 or 802.1x.
- 48V POE compatible for use with the supplied POE injector and other POE switches as well.
- A single panel can easily handle 32Mbps bandwidth.
- Two or more panels can be used to point to a single access point as long as they angle between panels is no more than 60°.
- Mountable on flat surfaces and on poles up to a 2" diameter. Longer bands available as an upgrade.

Dime	nsions	48mm			
	205mm		205mm		
205mm	PINCUT ·∯·	83.3mm	205mm		

	1						
	ECW-Long						
Chipset	Atheros AR9344 600MHz				WARRANTY		
Memory	DDR2 64MB	PYEAR					
Storage	8MB Flash			WARRANTY			
IC	SiGe5012B						
Port	10/100Mbps LAN*2						
Speed	300Mbps						
Transmission	DSSS						
Modulation	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK						
Standard	IEEE802.11n,IEEE802.11a ,IEEE802.3u						
Protocol	CSMA/CA,TCP/IP,IPX/SPX,NetBEUI,DHCP,NDIS3,NDIS4,NDIS5						
Channel	4920~ 6085MHz						
Power dissipation	≤6W						
Power	48V 0.5A						
		6-24Mbps 23:		23±2dBm	3±2dBm		
	802.11a	36-48Mbps		22±2dBm			
		54Mbp	bps 21±2dBm				
	802.11n	HT20	MCS 0-3	23±2dBm			
			MCS 4		22±2dBm		
			MCS 5		21.5±2dBm		
RF @25°C±2dB			MCS 6		21±2dBm		
			MCS 7		20.5±2dBm		
		HT40	MCS 0-3		22±2dBm		
			MCS 4		21.5±2dBm		
			MCS 5		21±2dBm		
			MCS 6		20.5±2dBm		
		MCS 7			20±2dBm		
	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73					
Sensitivity	202.44	HT20 MCS 0 ≤ -86; MCS 7 ≤ -68					
	802.11n	HT40 MCS 0 ≤ -83; MCS 7 ≤ -65			65		
	Frequency	4900~6100MHz					
Antenna	Polarization	Vertical / Horizontal					
	Gain	16DBi POE					
	WEP Management						
Manageret	SNMP MIB	Yes Injector					
Management	Telnet	Yes Included					
	Serial	Yes					
Canada	MAC Address Control No						
Security	Encryption WEP 64/128bits,WPA,WPA2,802.1x						
	Operating Temperature -30~65°C						
Operating Condition	Storage Temperature	-50∼80°C					
Condition	Humidity	≤95% (Non-condensed)					
Dimensions 205*205*132.3MM (8.07×8.07"×5.21")							

201 N. Elm St. Kemp, TX 75143



866-264-0041 sales@envirocams.com